

SAVOX HC-100 HELMET-COM HEADSET



Modular concept

> Excellent audio performance

Key Benefits

- Best in class audio performance
- Unique modularity one speaker part can host four different microphone options
- The microphone part can easily be changed according to the current user need
- Adapts to Savox Classic Remote Speaker Microphones and Push to Talks with 4-pole nexus type connector jack
- Boom microphone option can be rotated out of the way when the mic is not in use
- Rugged and durable design
- Adapts to a wide range of helmets

Savox HC-100 Helmet-Com is a versatile helmet mounted headset for professionals working in hazardous conditions, designed especially to meet the communication needs of fire fighters.

Savox HC-100 Helmet-Com headset offers ease-of-use and unique modularity; the user can choose from four different microphone options. This modularity along with great audio performance makes Savox HC-100 an excellent choice for versatile tasks.

APPLICATIONS

Ideal for professionals who wear a protective helmet, designed especially keeping in mind the various tasks of fire and emergency services personnel

- Fire fighting
- Emergency Services



MICROPHONE OPTIONS

Savox HC-100 offers unprecented modularity in a headset: the same speaker part can host four different microphone options and the user can choose the most suitable for the task at hand.

- Boom Microphone
- Short Microphone
- Bone Microphone
- Throat microphone



MOUNTING

Savox HC-100 is easily mounted into helmets, there are two different fixing options:

- Universal helmet adapter with unique Savox arm/strap
- MSA Gallet adapter (F1 FX helmet)

SAVOX HC-100 HELMET-COM HEADSET

Compatible with Classic RSM/PTTs 4 different microphone options

COMPATIBLE PTT/RSM UNITS

Savox HC-100 Helmet-Com headset connects to all Savox Classic Pushto-Talk and Remote Speaker Microphones (with QR4 quick release connector).

QR4	C-C440	C-C500	C-C550

Speaker housing	Mechanical
Weight	90g without helmet fixing parts
Material	Polyamide, TPU, Rubber
Fixing	Universal helmet fixing adapter, arm/strap, MSA Gallet F1 FX helmet adapter
Cable	Length 270 mm, diameter 4.6mm, tension strenght max. 50N

	Electrical
Speaker	32Ohm, Nominal 0,25W, SPL 81dB / 0,25W / 0,5m
Microphone	connector, 3.5mm socket
	Rotating microphone mechanism

	Environmental
Operating temperature	-40+80°C
Storage temperature	-20+80°C
Maximum humidity	90%
Drop	tested from 2 meters
Protection (dust&water)	Powerful water jet without damaging the headset
Electromagnet compatibility	Emissions: EN 55032 (CISPR 32) Immunity: EN 55035 (CISPR 35)

Boom Microphone

3.5mm connector, threaded nut attachment		
Weight 20g		
Max input level 120dB		
Sensitivity -46 +-2dB		
Electret, noise cancelling microphone, unidirectional		

Short Boom Microphone

Electret, omnidirectional Sensitivity -39 +-2dB Weight 12g 3.5mm connector, threaded nut attachment

Skull Microphone

Dynamic, vibration sensitive Impedance 6500Ω Weight 22g 3.5 mm connector

Throat Microphone

Dynamic, vibration sensitive
impedance 6500 Ω , parallel 300 Ω
Weight 30g
3.5mm connector
Throat band with velcro style fixing